

1160 HSSCO DIN 338 S



Avance/Feed	P				M		K			N				S		H		
	<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
	● 25-45	● 18-30	● 10-25		○ 12-20					● 45-100		● 70-90						
	0,02-0,06	0,02-0,03	0,01-0,04		0,01-0,04					0,02-0,05		0,02-0,04						
Ø2	0,02-0,06	0,02-0,03	0,01-0,04		0,01-0,04					0,02-0,05		0,02-0,04						
Ø5	0,08-0,12	0,05-0,07	0,04-0,09		0,05-0,09					0,05-0,12		0,05-0,09						
Ø10	0,12-0,30	0,12-0,18	0,09-0,18		0,14-0,21					0,18-0,24		0,18-0,21						
Ø15	0,18-0,40	0,18-0,24	0,12-0,28		0,20-0,28					0,20-0,32		0,20-0,28						
Ø20	0,22-0,46	0,22-0,28	0,14-0,33		0,22-0,33					0,25-0,37		0,25-0,33						

Vc (m/min). ● Optima / Optimun ○ Alternativo / Alternative



Ø mm	L mm	l mm	
2,00	49	24	1
2,10	49	24	1
2,20	53	27	1
2,30	53	27	1
2,40	57	30	1
2,50	57	30	1
2,60	57	30	1
2,70	61	33	1
2,80	61	33	1
2,90	61	33	1
3,00	61	33	1
3,10	65	36	1
3,20	65	36	1
3,30	65	36	1
3,40	70	39	1
3,50	70	39	1
3,60	70	39	1
3,70	70	39	1
3,80	75	43	1
3,90	75	43	1
4,00	75	43	1
4,10	75	43	1
4,20	75	43	1
4,30	80	47	1
4,40	80	47	1
4,50	80	47	1
4,60	80	47	1
4,70	80	47	1
4,80	86	52	1
4,90	86	52	1
5,00	86	52	1
5,10	86	52	1
5,20	86	52	1
5,30	86	52	1
5,40	93	57	1
5,50	93	57	1
5,60	93	57	1
5,70	93	57	1
5,80	93	57	1
5,90	93	57	1

Ø mm	L mm	l mm	
6,00	93	57	1
6,10	101	63	1
6,20	101	63	1
6,30	101	63	1
6,40	101	63	1
6,50	101	63	1
6,60	101	63	1
6,70	101	63	1
6,80	109	69	1
6,90	109	69	1
7,00	109	69	1
7,10	109	69	1
7,20	109	69	1
7,30	109	69	1
7,40	109	69	1
7,50	109	69	1
7,60	117	75	1
7,70	117	75	1
7,80	117	75	1
7,90	117	75	1
8,00	117	75	1
8,10	117	75	1
8,20	117	75	1
8,30	117	75	1
8,40	117	75	1
8,50	117	75	1
8,60	125	81	1
8,70	125	81	1
8,80	125	81	1
8,90	125	81	1
9,00	125	81	1
9,50	125	81	1
9,80	133	87	1
10,00	133	87	1
10,50	133	87	1
11,00	142	94	1
11,50	142	94	1
12,00	151	101	1
12,50	151	101	1
13,00	151	101	1