

2322

HSS DIN 352

Perfil completo / Profil complet / Non serial form

UNC
 ANSI/ASME
 B1.1




Tol.
2B

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
•									•	•							

Vc (m/min). ● Optima / Optimun ○ Alternativo / Alternative

Macho 3°
 Taraud 3°
 Tap 3°
 Gewindebohrer 3°

PVP = € / 3 < M (€ / 3)
 MF (€ / 2)



Ø	P	Nº	L mm	I mm	mm	d mm
Nº6	32,00	3	45	14	3,00	4,0
Nº10	24,00	3	50	16	4,90	6,0
1/4	20,00	3	50	19	4,90	6,0
5/16	18,00	3	56	22	4,90	6,0
3/8	16,00	3	70	24	5,50	7,0
7/16	14,00	3	70	24	6,20	8,0

Ø	P	Nº	L mm	I mm	mm	d mm
1/2	13,00	3	75	29	7,00	9,0
9/16	12,00	3	80	30	9,00	11,0
5/8	11,00	3	80	32	9,00	12,0
3/4	10,00	3	95	40	11,00	14,0
7/8	9,00	3	100	40	14,50	18,0
1"	8,00	3	110	50	14,50	18,0

*Hasta fin de existencias / Jusqu'à épuisement des stocks / Until end of stock