


2501

HSS DIN EN 22568

M-MF
DIN 13Tol.
6g

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
•									•	•							

Vc (m/min). • Optima / Optimun ○ Alternativo / Alternative



PVP = € + 10%

Ø	P	D mm	E mm	
** M1,0	0,25	16	5	1
** M1,1	0,25	16	5	1
** M1,2	0,25	16	5	1
** M1,4	0,30	16	5	1
M1,6	0,35	16	5	1
M1,7	0,35	16	5	1
M1,8	0,35	16	5	1
M2,0	0,40	16	5	1
M2,2	0,45	16	5	1
M2,3	0,40	16	5	1
M2,5	0,45	16	5	1
M2,6	0,45	16	5	1
M3,0	0,50	20	5	1
M3,0	0,60	20	5	1
M3,5	0,60	20	5	1
*M3,5	0,75	20	5	1
M4,0	0,50	20	5	1
M4,0	0,70	20	5	1
M4,5	0,75	20	7	1
M5,0	0,50	20	5	1
M5,0	0,75	20	7	1
M5,0	0,80	20	7	1
M5,5	0,90	20	7	1
M6,0	0,50	20	7	1
M6,0	0,75	20	7	1
M6,0	1,00	20	7	1
M7,0	0,75	25	9	1
M7,0	1,00	25	9	1
M8,0	0,50	25	9	1
M8,0	0,75	25	9	1
M8,0	1,00	25	9	1
M8,0	1,25	25	9	1
M9,0	1,00	25	9	1
M9,0	1,25	25	9	1
M10,0	0,50	30	11	1
M10,0	0,75	30	11	1
M10,0	1,00	30	11	1
M10,0	1,25	30	11	1
M10,0	1,50	30	11	1
M11,0	0,75	30	11	1
M11,0	1,00	30	11	1
M11,0	1,25	30	11	1
M11,0	1,50	30	11	1
M12,0	0,75	38	10	1
M12,0	1,00	38	10	1
M12,0	1,25	38	10	1
M12,0	1,50	38	10	1

** Tol. 6h

Ø	P	D mm	E mm	
M12,0	1,75	38	14	1
M13,0	0,75	38	10	1
M13,0	1,00	38	10	1
M13,0	1,50	38	10	1
M13,0	1,75	38	14	1
M14,0	0,75	38	10	1
M14,0	1,00	38	10	1
M14,0	1,25	38	10	1
M14,0	1,50	38	10	1
M14,0	2,00	38	14	1
M15,0	1,00	38	10	1
M15,0	1,50	38	10	1
M15,0	2,00	38	14	1
M16,0	1,00	45	14	1
M16,0	1,25	45	14	1
M16,0	1,50	45	14	1
M16,0	2,00	45	18	1
M17,0	1,00	45	14	1
M17,0	1,25	45	14	1
M17,0	1,50	45	14	1
M18,0	1,00	45	14	1
M18,0	1,25	45	14	1
M18,0	1,50	45	14	1
M18,0	2,00	45	14	1
M18,0	2,50	45	18	1
M19,0	1,00	45	14	1
M19,0	1,25	45	14	1
M19,0	1,50	45	14	1
M20,0	1,00	45	14	1
M20,0	1,25	45	14	1
M20,0	1,50	45	14	1
M20,0	2,00	45	14	1
M20,0	2,50	45	18	1
M21,0	1,00	45	16	1
M21,0	1,25	45	14	1
M21,0	1,50	45	14	1
M22,0	1,00	55	16	1
M22,0	1,25	55	16	1
M22,0	1,50	55	16	1
M22,0	2,00	55	16	1
M22,0	2,50	55	22	1
M23,0	1,50	55	16	1
M24,0	1,00	55	16	1
M24,0	1,25	55	16	1
M24,0	1,50	55	16	1
M24,0	2,00	55	16	1
M24,0	3,00	55	22	1

(continúa Ref.2501 / suite Réf.2501 / Ref.2501 cont'd)



2501

HSS DIN EN 22568

M-MF
DIN 13Tol.
6g

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
●									●	●							

Vc (m/min). ● Optima / Optimun ○ Alternativo / Alternative



PVP = € + 10%

Ø	P	D mm	E mm	
M25,0	1,00	55	16	1
M25,0	1,50	55	16	1
M26,0	1,00	55	16	1
M26,0	1,50	55	16	1
M26,0	2,00	55	16	1
M27,0	1,00	65	18	1
M27,0	1,50	65	18	1
M27,0	2,00	65	18	1
M27,0	3,00	65	25	1
M28,0	1,00	65	18	1
M28,0	1,50	65	18	1
M28,0	2,00	65	18	1
M30,0	1,00	65	18	1
M30,0	1,50	65	18	1
M30,0	2,00	65	18	1
M30,0	3,50	65	25	1
M32,0	1,00	65	18	1
M32,0	1,50	65	18	1
M32,0	2,00	65	18	1
M33,0	1,50	65	18	1
M33,0	2,00	65	18	1
M33,0	3,50	65	25	1
M34,0	1,50	65	18	1
*M34,0	2,00	65	18	1
M35,0	1,50	65	18	1
M35,0	2,00	65	18	1
M36,0	1,50	65	18	1
M36,0	2,00	65	18	1
M36,0	3,00	65	25	1
M36,0	4,00	65	25	1

Ø	P	D mm	E mm	
M38,0	1,50	75	20	1
M38,0	2,00	75	20	1
M39,0	1,50	75	20	1
M39,0	2,00	75	20	1
M39,0	3,00	75	30	1
M39,0	4,00	75	30	1
M40,0	1,50	75	20	1
M40,0	2,00	75	20	1
*M40,0	3,00	75	30	1
M42,0	1,50	75	20	1
M42,0	2,00	75	20	1
M42,0	3,00	75	30	1
M42,0	4,50	75	30	1
M45,0	1,50	90	22	1
M45,0	2,00	90	22	1
M45,0	3,00	90	36	1
*M45,0	4,50	90	36	1
M48,0	1,50	90	22	1
M48,0	2,00	90	22	1
M48,0	3,00	90	36	1
M48,0	5,00	90	36	1
M50,0	1,50	90	22	1
M52,0	1,50	90	22	1
M52,0	2,00	90	22	1
M52,0	3,00	90	36	1
M52,0	5,00	90	36	1
M56,0	5,50	105	36	1
M60,0	5,50	105	36	1
M63,0	1,50	105	22	1
M64,0	6,00	120	36	1

*Hasta fin de existencias / Jusqu'à épuisement des stocks / Until end of stock