

2501/5

HSS DIN EN 22568

Izquierda / A gauche / Left hand


M-MF
DIN 13

Tol.
6g

LH

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
•									•	•							

Vc (m/min). • Optima / Optimun ○ Alternativo / Alternative



PVP = € + 10%

Ø	P	D mm	E mm	
M3,0	0,50	20	5	1
M4,0	0,70	20	5	1
M5,0	0,80	20	7	1
M6,0	1,00	20	7	1
M7,0	1,00	25	9	1
M8,0	1,00	25	9	1
M8,0	1,25	25	9	1
M10,0	1,00	30	11	1
M10,0	1,25	30	11	1
M10,0	1,50	30	11	1
M12,0	1,25	38	10	1
M12,0	1,50	38	10	1
M12,0	1,75	38	14	1
M14,0	1,50	38	10	1

Ø	P	D mm	E mm	
M14,0	2,00	38	14	1
M16,0	1,50	45	14	1
M16,0	2,00	45	18	1
M18,0	1,50	45	14	1
M18,0	2,50	45	18	1
M20,0	1,50	45	14	1
M20,0	2,50	45	18	1
M22,0	1,50	55	16	1
M22,0	2,50	55	22	1
M24,0	1,50	55	16	1
M24,0	3,00	55	22	1
M27,0	3,00	65	25	1
M30,0	3,50	65	25	1