


3170

HM-MD DIN 6527 L




Vc (m/min)	P				M		K			N				S		H		
	<800 110-250	<1.000 90-200	<1.200 75-180	<1.400 60-120	<950 70-110	<1.200 60-100	<500 120-180	<800 100-140	<1.400 60-120	Al	Cu	Mg/Zn	Plastic	Ni 40-80	Ti 60-110	50 HRC	55 HRC	60 HRC
K	0,7	0,7	0,7	0,7	0,7	1,3	1,3	1,3	1,3	1,3	1,3	0,7	0,7	0,7	0,7	0,7	0,7	0,7
fz	Ap	Ae	Ø1	Ø2	Ø3	Ø4	Ø5	Ø6	Ø8	Ø10	Ø12	Ø14	Ø16	Ø18	Ø20	Ø25	Ø32	Ø40
	1																	
	2																	
	3																	
	4	0,5xØ	0,5xØ	-	-	0,045	0,060	0,075	0,090	0,120	0,150	0,180	0,210	0,240	0,270	0,300		
	5																	
	6																	

vf(mm/min) = rpm x Z x fz x K
rpm = (Vc x 1000) / (Ø x π)

● Optima / Optimun ○ Alternativo / Alternative

Fresado
Fraisage
Milling
Fräsen



Ø mm	d mm	L mm	l mm	Z	
3,00	6	57	7	2	1
4,00	6	57	8	2	1
5,00	6	57	10	2	1
6,00	6	57	10	2	1
8,00	8	63	16	2	1
10,00	10	72	19	2	1

Ø mm	d mm	L mm	l mm	Z	
12,00	12	83	22	2	1
14,00	14	83	22	2	1
16,00	16	92	26	2	1
18,00	18	92	26	2	1
20,00	20	104	32	2	1