

3202

Cilíndrica con corte / Cylindrique taillée / Straight with cut



	P				M		K			N				S		H		
	<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
CRUZ	● 400-800	● 400-800	○ 300-700		● 600-1000	○ 400-800	● 450-800	● 400-800			● 400-800	● 400-800		○ 400-800	● 600-1000			
DIAM	○ 400-800	● 400-800	● 300-700	● 300-700	○ 600-1000	● 400-800	● 500-800	● 400-800	● 300-700		○ 300-800		○ 300-700	● 300-800	● 300-1000	● 200-600	● 200-600	
ALU										● 300-1000	● 300-700	○ 400-1000	● 400-1000					

Vc (m/min). ● Optima / Optimun ○ Alternativo / Alternative



Ø mm	d mm	CRUZ	DIAM	ALU	L mm	l mm	
3,00	3				38	13	1
4,00	4				50	13	1
6,00	6				50	19	1
8,00	6				65	19	1

Ø mm	d mm	CRUZ	DIAM	ALU	L mm	l mm	
10,00	6				65	19	1
12,00	6				70	25	1
16,00	6				70	25	1