

4101

HSS DIN ≈ 206

Form.
B



Tol.
H7

ISO
236

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
•						•	•		•	•		•					

Vc (m/min). • Optima / Optimun ○ Alternativo / Alternative



Ø mm	L mm	l mm	
1,50	41	20	1
2,00	50	25	1
2,25	54	27	1
2,50	58	29	1
2,75	62	31	1
3,00	62	31	1
3,25	66	33	1
3,50	71	35	1
3,75	71	35	1
4,00	76	38	1
4,25	76	38	1
4,50	81	41	1
4,75	81	41	1
5,00	87	44	1
5,25	87	44	1
5,50	93	47	1
5,75	93	47	1
6,00	93	47	1
6,25	100	50	1
6,50	100	50	1
6,75	107	54	1
7,00	107	54	1
7,25	107	54	1
7,50	107	54	1
7,75	115	58	1
8,00	115	58	1
8,25	115	58	1
8,50	115	58	1
8,75	124	62	1
9,00	124	62	1
9,25	124	62	1
9,50	124	62	1
9,75	133	66	1
10,00	133	66	1
10,25	133	66	1
10,50	133	66	1
10,75	142	71	1
11,00	142	71	1
11,25	142	71	1
11,50	142	71	1
11,75	142	71	1
12,00	152	76	1

Ø mm	L mm	l mm	
12,50	152	76	1
13,00	152	76	1
13,50	163	81	1
14,00	163	81	1
14,50	163	81	1
15,00	163	81	1
15,50	175	87	1
16,00	175	87	1
16,50	175	87	1
17,00	175	87	1
17,50	188	93	1
18,00	188	93	1
18,50	188	93	1
19,00	188	93	1
19,50	201	100	1
20,00	201	100	1
20,50	201	100	1
21,00	201	100	1
21,50	215	107	1
22,00	215	107	1
22,50	215	107	1
23,00	215	107	1
23,50	215	107	1
24,00	231	115	1
24,50	231	115	1
25,00	231	115	1
25,50	231	115	1
26,00	231	115	1
26,50	231	115	1
27,00	247	124	1
27,50	247	124	1
28,00	247	124	1
28,50	247	124	1
29,00	247	124	1
29,50	247	124	1
30,00	247	124	1
32,00	265	133	1
34,00	284	142	1
36,00	284	142	1
38,00	305	152	1
40,00	305	152	1