

7139

TCT

L=35



WELDON
19

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
●	●	●	●	●	○	●	●	●	○	●	○	○	●	●	●	○	
40-65	30-40	20-25	15-20	20-30	15-20	50-60	45-55	15-20	70-90	40-90	50-60	70-90	15-20	15-30	20-25	15-20	

Vc (m/min). ● Optima / Optimun ○ Alternativo / Alternative



Ø mm	d mm	L mm	
18,00	19	35	1
19,00	19	35	1
20,00	19	35	1
21,00	19	35	1
22,00	19	35	1
23,00	19	35	1
24,00	19	35	1
25,00	19	35	1
26,00	19	35	1

Ø mm	d mm	L mm	
27,00	19	35	1
28,00	19	35	1
29,00	19	35	1
30,00	19	35	1
31,00	19	35	1
32,00	19	35	1
33,00	19	35	1
34,00	19	35	1
35,00	19	35	1

7139

TCT

L=50



WELDON
19

P				M		K			N				S		H		
<800	<1.000	<1.200	<1.400	<950	<1.200	<500	<800	<1.400	Al	Cu	Mg/Zn	Plastic	Ni	Ti	50 HRC	55 HRC	60 HRC
●	●	●	●	●	○	●	●	●	○	●	○	○	●	●	●	○	
40-65	30-40	20-25	15-20	20-30	15-20	50-60	45-55	15-20	70-90	40-90	50-60	70-90	15-20	15-30	20-25	15-20	

Vc (m/min). ● Optima / Optimun ○ Alternativo / Alternative



Ø mm	d mm	L mm	
18,00	19	50	1
19,00	19	50	1
20,00	19	50	1
21,00	19	50	1
22,00	19	50	1
23,00	19	50	1
24,00	19	50	1
25,00	19	50	1
26,00	19	50	1
27,00	19	50	1
28,00	19	50	1
29,00	19	50	1
30,00	19	50	1
31,00	19	50	1
32,00	19	50	1
33,00	19	50	1
34,00	19	50	1

Ø mm	d mm	L mm	
35,00	19	50	1
36,00	19	50	1
37,00	19	50	1
38,00	19	50	1
39,00	19	50	1
40,00	19	50	1
41,00	19	50	1
42,00	19	50	1
43,00	19	50	1
44,00	19	50	1
45,00	19	50	1
46,00	19	50	1
47,00	19	50	1
48,00	19	50	1
49,00	19	50	1
50,00	19	50	1